



CHERY MOTOR OIL

5W-40

Engine oil for CHERY
passenger cars

Specification

- API SP
- ACEA A3/B4

Product description

Premium engine oil based on synthetic technology. The product is specially intended for modern engines of CHERY passenger cars including engines fitted with turbo-charger.

Product description

Recommended for all-season use in gasoline engines (without particulate filters) for CHERY cars both during warranty and after-warranty periods.

Benefits

MAXIMUM PROTECTION

Suitable for extreme start stop, idling and traffic jam conditions

ENGINE CLEANLINESS

Great dispersant and detergent properties prevent deposits formation on engine parts

EASY COLD START

Excellent low-temperature properties of synthetic base oils provide easy cold start

Property	Test methods	CHERY MOTOR OIL 5W-40
Kinematic viscosity at 100°C, mm ² /s	GOST 33 / ASTM D445	14,5
Viscosity index	GOST 25371 / ASTM D 2270	166
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST 52559	4 400
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST 52257	38 500
Total Base Number, mg KOH/g	GOST 30050 / ASTM D2896	10,0
Sulphated Ash, %mass	GOST 12417 / ASTM D874	1,1
Noack evaporation loss, %	ASTM D5800 / DIN 51561-1	9,8
Flash Point, COC, °C	GOST 4333 / ASTM D92	234
Pour Point, °C	GOST 20287 (method B)	-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.